



Mercedes-Benz

AP00.20-U-1208RAC SERVICE SHEET for Mercedes-Benz Maintenance System (USA)

MODEL 251
diesel models only

Light Truck Model Year 2008
USA

Model 251



Customer: _____

Repair order number: _____

First visit at 1,000 - 3,000 miles Performed YES [] NO []

Tire Rotation (non-staggered width wheel setup only) Performed in accordance with the tire manufacturer's recommended intervals Tires rotated YES [] NO []


Tire Inspection (staggered and non-staggered width wheel set up) Inspect tires for damage and correct tire inflation pressure Tires inspected YES [] NO []

Current mileage reading: _____ Oil grade/viscosity: _____

Additional notes: _____

Service work to be performed as advised by service advisor: _____ Completion date: _____ Confirm work has been performed by signing below: _____

Information icon: US Service 4 through US Service 20 apply to "Additional work" items only. Vehicle determines need for US Service 3 (Engine oil and filter change) as well as US Service 1 or US Service 2 Perform each service as described.

US Service 1 ↓ 	first at 10,000 mi or 1 year; after first every 20,000 mi or 2 years	
US Service 2 ↓	first at 20,000 mi or 2 years; after first every 20,000 mi or 2 years	Not OK ↓
	Interior - Required	
<input type="checkbox"/>	<input type="radio"/> Reset service indicator in instrument cluster	AP00.20-P-0042RT
	<input type="checkbox"/> Check parking brake (function test only)	<input type="checkbox"/>
	Interior - Recommended Function test	
<input type="checkbox"/>	<input type="radio"/> Horn	<input type="checkbox"/>
<input type="checkbox"/>	<input type="radio"/> Warning/indicator lamps, illumination and interior lighting	<input type="checkbox"/> AP54.30-P-5452C
<input type="checkbox"/>	<input type="radio"/> Windshield wipers, windshield washer system, headlamp cleaning system	<input type="checkbox"/> AP82.30-P-8252RT
	<input type="radio"/> Check seat belts and buckles for signs of external damage and proper function	<input type="checkbox"/> AP91.40-P-9150RT
<input type="checkbox"/>	<input type="radio"/> Battery, check battery condition using "Midtronics MCR 717" tester. Attach Midtronics MCR 717 Test Report print out here.	<input type="checkbox"/> AP54.10-U-5453A
	Wheels, brakes - Required	
<input type="checkbox"/>	<input type="radio"/> Check thickness of brake pads, front and rear	<input type="checkbox"/> AP42.10-P-4253A
<input type="checkbox"/>	<input type="radio"/> Correct tire inflation pressure and enter in bar or psi. LF RF LR RR bar/psi: _____	<input type="checkbox"/>
	Wheels, brakes - Recommended	
<input type="checkbox"/>	<input type="radio"/> Inspect tires for damage and splits, measure tread depth, record in mm: LF RF LR RR outside _____ center _____ inside _____	<input type="checkbox"/> AP40.10-P-4051RT
	Underside of vehicle - Required	
	<input type="radio"/> Leakage - Major components Check for chafe marks, line routing, damaged components <input type="checkbox"/> In the event of leakage, determine cause and perform repair via separate work order	<input type="checkbox"/> AP00.20-P-0053RT
	<input type="radio"/> Check front axle ball joints for play, check rubber boots	<input type="checkbox"/> AP33.20-P-3353RT
	<input type="radio"/> Check rear axle ball joints for play, check rubber boots	<input type="checkbox"/> AP35.20-P-3555RT
	<input type="radio"/> Inspect play of tie rod and drag link joints, inspect rubber boots	<input type="checkbox"/> AP46.00-P-4653RT

US Service 1 ↓	US Service 2 ↓		Not OK ↓
		Vehicle front/rear - Recommended	
<input type="checkbox"/>	<input type="radio"/>	Check wiper blade condition	<input type="checkbox"/> AP82.30-P-8253G
	<input type="radio"/>	Check and correct headlamp setting	<input type="checkbox"/> AP82.10-P-8260RT
		Engine compartment - Required	
	<input type="radio"/>	Leakage - Major components Check for chafe marks, line routing, damaged components i In the event of leakage, determine cause and perform repair via separate work order	<input type="checkbox"/> AP00.20-P-0053RT
<input type="checkbox"/>	<input type="radio"/>	Check catch, safety catch and hinges on engine hood for proper operation.	<input type="checkbox"/> AP88.40-P-8851RT
<input type="checkbox"/>	<input type="radio"/>	Clean water drain in air/water duct	AP83.10-P-8339M
	<input type="radio"/>	Check condition of poly-V-belt	<input type="checkbox"/> AP13.22-P-1352RTD
		Check fluid level, correct as required i If there is a loss of fluid, determine cause and perform repair via separate work order	
<input type="checkbox"/>	<input type="radio"/>	Brake system	<input type="checkbox"/> AP42.10-P-4210RT
	<input type="radio"/>	Power steering	<input type="checkbox"/> AP46.00-P-4611RT
<input type="checkbox"/>	<input type="radio"/>	Windshield washer system (incl. summer/winter cleanser)	AP82.35-P-8210RT
	<input type="radio"/>	Drain fuel filter	AP47.20-P-0794A
	<input type="radio"/>	Clean water drain in air/water duct	AP83.10-P-8339M
		Additional Work	
Completed <input checked="" type="checkbox"/>			Not OK ↓
US Service 3 Required	every 10,000 mi or 1 year: Engine compartment	<input type="checkbox"/> Engine - oil and filter change	AP18.00-P-0101TQ
US Service 4 Required	every 2 years: Engine compartment	<input type="checkbox"/> Replace brake fluid	AP42.00-P-4280RT
US Service 4 Recommended	every 2 years:	<input type="checkbox"/> Check bodywork for paint work damage by service advisor	<input type="checkbox"/> AP98.00-P-9850RT
	Underside of vehicle	<input type="checkbox"/> Chassis and load-bearing body components: Check for damage and corrosion by service advisor	<input type="checkbox"/> AP00.20-P-0090SX
US Service 5 Required	every 30,000 mi or 2 years: Passenger compartment	<input type="checkbox"/> Replace combination filter	AP83.00-P-8384RT

Completed <input checked="" type="checkbox"/>	Not OK
↓	↓
US Service 6 and 7	not applicable
US Service 8 Required	every 40,000 mi or 4 years: Engine compartment
<input type="checkbox"/> Replace engine air-cleaner insert	AP09.10-P-0980RTD
US Service 9	not applicable
US Service 10 Recommended	every 3 years: Passenger compartment
<input type="checkbox"/> Panorama sliding roof: Clean and lubricate guide mechanism	AP77.20-P-7732RT
US Service 11 Required	every 20,000 mi or 2 years: Engine compartment
<input type="checkbox"/> Replace fuel filter	AP47.20-P-0780RTD
US Service 13 Required	every 150,000 mi or 15 years: Engine compartment
<input type="checkbox"/> Replace coolant	AP20.00-P-2080RTD
US Service 14-19	not applicable
US Service 20 Required	once at 40,000 mi: Underside of vehicle
<input type="checkbox"/> Automatic transmission - oil and filter change	AP27.00-P-2702W